Material Safety Data Sheet

80801 Sto Primer Sand

Section I - Manufacturer's Information

Identity: Sto Primer Sand Common Name/Synonym: Waterbased Acrylic Coating

Manufacturer's Sto Corp. Information #: (404) 346-3666 DOT Hazardous Class: Not Regulated Name: 6175 Riverside Drive, SW Emergency #: (800) 424-9300 CAS Number: Not Registered

Atlanta, GA 30331

Section II - Preparation Information

Sto Corp. Research and Development Department Prepared Date Prepared: 05-Apr-13

Section III - Hazardous Ingredients

Component - A	TWA/TLV						
Ingredient		CAS Number	OSHA	ACGIH	Other	LD50	LC50
Calcium Carbonate	15-40	1317-65-3	15 mg/m³	10 mg/m³	N/E mg/m³	N/E	N/E
Silicon Dioxide	10-30	14808-60-7	10/(%SiO2+2) mg/m ³	0.10 mg/m³	NIOSH 0.05 mg/m ³	N/E	N/E
Hydrous Magnesium Silicate	1-5	14807-96-6	2.0 mg/m ³	2.0 mg/m ³	N/E mg/m³	N/E	N/E
Titanium Dioxide	5-10	13463-67-7	15.0 mg/m ³	10.0 mg/m ³	N/E mg/m³	N/E	N/E

Section IV - Physical/Chemical Characteristics

Component - A

Boiling Point: N/A VaporDensity N/E pH Level: 7.5 - 10.0 Vapor Pressure: N/E Melting Point: N/A Evaporation Rate < 1 Physical State: Liquid Solubility in Water: Miscible

Freezing 0 deg C/32 deg F Specific Gravity: [H2O=1]: > 1.0 Odor Threshold: N/E Appearance and Odor: Viscous Liquid - Slight Odor Coefficient of Water/Oil Distribution: N/E

Section V - Fire and Explosion Hazard Data

Component - A

Flammability: N/A Flash Point: N/A Autoignition Temperature: N/A Limits LEL/UEL: N/E - N/E Sensitivity to impact: None Sensitivity to Static Discharge: None

Hazardous Decomposition

Products: COx, NOx, Smoke, Hydrocarbons

Unusual Fire and

Explosive Hazards: Material may spatter above 100 deg C/212 deg F Extinguishing Media: Water spray, foam, dry chemical

Special Firefighting

Procedures: SCBA, full protective gear

Section VI - Reactivity Data

Component - A

Hazardous Decomposition Products: None Stability: Stable Incompatibility (Materials to Avoid): None Hazardous Polymerization: None Conditions to Avoid: None

Section VII - Health Hazard Data

IARC: No OSHA Regulated: No LD50: N/A LC50: N/A Carcinogencity: No NTP: No

Effects and Hazards of

Eye Contact: Direct contact with material may cause irritation.

Effects and Hazards of

Product is waterbased. For normal application, inhalation is not expected to be a primary route of exposure. Consult Section Inhalation (Breathing):

IX - Precautions for Safe Handling and Use for further details.

Page 1 of 2

Material Safety Data Sheet

80801 Sto Primer Sand

Effects and Hazards of

Skin Contact: Contact with skin may cause reddening or a slight rash in individuals with sensitive skin.

Effects and Hazards of May cause some stomach distress.

Ingestion (Swallowing):

HMIS Health: Flammability: Reactivity: 0 PPF:

Section VIII - Emergency and First Aid Procedures

Treatment for Eye

As with any foreign material in the eyes, they should be flushed for fifteen minutes with running water while holding the eyes Contact:

open. This will assist in flushing material from the eye. If irritation continues, seek medical attention.

Treatment for Inhalation

(Breathing): If respiratory irritation occurs, go to fresh air. Flood work area with fresh air and if irritation continues, seek medical attention

Treatment for Skin

Contact: Wash with mild soap and water. Hand creams should be used to prevent dry skin. If skin irritation, reddening or a rash

occur, seek medical attention.

Treatment for Ingestion Contact medical help immediately; untrained first aid personnel should not attempt to administer first aid.

(Swallowing):

Section IX - Precautions for Safe Handling and Use

Steps to be taken in case

material is released or

spilled (Dry Stage): Sweep and dispose of in proper receptacle.

Steps to be taken in case

material is released or

spilled (Wet Stage): Scoop into proper receptacle and allow to harden.

Waste Disposal

Method: Per local, state and federal regulations.

Precautions To Be Taken

In Handling and Storing: Store in a cool dry location, out of direct sunlight. Protect from freezing.

Other Precautions: This material is an industrial product designed to be used by professionals familar with the requirements of this material safety

data sheet.

Respiratory protection is not required for normal use of this product. Product contains silica (quartz) sand, which has been Respiratory Protection:

designated by IARC as a group 1 - human carcinogen. Prolonged exposure to respirable silica (quartz) dust may cause delayed (chronic) lung injury such as silicosis. If material is ground upon or sanded when it is dry, NIÓSH/MSHÁ approved respirators for dust should be provided and worn. All workers required to use respiratory protection should be trained in their

proper selection, use and care.

Ventilation: Recommended; local or mechanical when mixing, applying or sanding the product in the dry state.

Protective Gloves: Recommended: plastic or rubber.

Eye Protection: Recommended; chemical splash safety goggles.

Other Protective

Recommended; spalsh bib and protective clothing. Equipment:

Work and Hygienic

Remove and wash contaminated clothing. As with all commercial and industrial products, always wash hands before eating or Practices:

smoking.

California Proposition 65: This product contains crystalline silica (quartz sand), which is considered a carcinogen by the State of California.

The information and recommendations contained herein are, to the best of Sto Corp.'s knowledge and belief, accurate and reliable as of the date issued. Sto Corp. does not warrant or guarantee their accuracy or reliability, and Sto Corp. shall not be liable for any loss or damage arising out of their use thereof. The information and recommendations are offered for the users' consideration and examination, and it is the users' responsibility to satisfy itself that they are suitable and complete for its particular use.